

# About Your Filtration System...

## Water Filter Removal and Installation



### WARNING

To avoid serious illness or death, do not use unit where water is unsafe or of unknown quality without adequate disinfection before or after use of filter.



### CAUTION

- If water filtration system has been allowed to freeze, replace filter cartridge.
- If system has not been used for several months, and water has an unpleasant taste or odor, flush system by dispensing 2-3 glasses of water. If unpleasant taste or odor persists, change filter cartridge.

## Replacing Water Filter

Cartridge needs to be replaced after 750 gallons of water (2838 liters) or 1 year of use, whichever comes first. Local water quality may affect rated life of filter.

1. Protect floor from possible water spill.
2. Turn cartridge counterclockwise until it releases from filter head.
3. Pull cartridge down and discard.
4. Inspect O-Rings on head for visible damage or wear.  
Replace with part No. R0185015 if necessary.
5. Write date of installation on replacement cartridge.
6. Push new cartridge into head.
7. Turn cartridge clockwise until cartridge stops.
8. Discard first 3 batches of ice after replacing cartridge.

## Troubleshooting

- Cloudy or colored water. Cloudy appearance in treated water is caused by air bubbles trapped in water. This does not affect cartridge performance and will disappear with use.
- Flakes in cold water or ice. Concentrations of minerals in water will form particles when water becomes frozen and melts. Particles are not harmful.
- Slow water flow rate. Cartridge has reached its capacity. Replace cartridge.
- Low water pressure. Confirm water pressure at unit without filter installed is a minimum of at least 35 pounds per square inch (244 kilopascals). Correct water pressure.
- Unusual taste. Cartridge has reached its capacity. Replace cartridge.
- Black particles in ice cubes. Initial water ejected through cartridge may contain black particles of harmless carbon dust flushed from cartridge. Particles are safe for consumption.

### Replacement Water Filter Limited One Year Warranty.

Maytag Appliances will repair or replace, free of charge, any part which is defective due to workmanship or materials for:

- Multistage cartridge: 12 months from date of purchase when defect is due to workmanship or materials.

### Warranty Limitations

- Not responsible for replacement caused by local poor water quality.
- Begins at date of original purchase.
- Applies to product used within United States.
- Service must be performed by an authorized Amana technician.

### Warranty Is Void If

- Product is used on a commercial, rental or leased basis.
- Product has defect or damage due to product accident, alteration, fire, flood, lightning, shipping and handling, or other conditions beyond the control of Maytag Appliances.
- Product is improperly installed or used.

### Owner's Responsibilities

- Provide proof of purchase (sales receipt).
- Provide normal care and maintenance.
- Replace owner replaceable items where directions appear in Installation and Operating Instructions.

### In no event shall Maytag Appliances be liable for incidental or consequential damages.

\*This warranty gives you specific legal rights and you may have others which vary from state to state. For example, some states do not allow the exclusion or limitation of incidental or consequential damages so this exclusion may not apply to you.

## How do I order a replacement filter cartridge?

To purchase replacement water filter cartridge, visit your local dealer or parts distributor. In the US, you may also call 1-877-232-6771 and ask for filter 67003662. Outside the US, contact your local appliance dealer or parts distributor.

**IMPORTANT:** Condition of water and amount used determines life span of water filter cartridge. If water use is high, or if water is of poor quality, replacement may need to take place more often.

# Water Filter Data

System Specification and Performance Data Sheet Replacement Water Filter Cartridge Model 67003662

## Specifications

Service Flow Rate (Maximum) .....	0.78 GPM (2.9 L/min)
Rated Service Life R0185011 (Maximum).....	750 gallons/ 2838 liters
Maximum Operating Temperature .....	100° F/38° C
Minimum Pressure Requirement.....	35 psi/ 138 kPa
Minimum Operating Temperature .....	33° F/1° C
Maximum Operating Pressure.....	120psi / 827kPa

**General Use Conditions:** Read this Performance Data Sheet and compare the capabilities of this unit with your actual water treatment needs.

Note that while the testing was performed under standard laboratory conditions, actual performance may vary. Systems must be installed and operated in accordance with manufacturer's recommended procedures and guidelines.

**DO NOT use this product where water is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. System certified for cyst reduction may be used on disinfected water that may contain filterable cysts.**

**USE ONLY WITH COLD WATER SUPPLY. CHECK FOR COMPLIANCE WITH THE STATE AND LOCAL LAWS AND REGULATIONS.**

Amana Clean 'n Clear retractable water filtration system uses a 67003662 replacement cartridge. Timely replacement of filter cartridge is essential for performance satisfaction from this filtration system. Please refer to the applicable section of your owner's manual for general operation, maintenance requirements and troubleshooting.

This system has been tested according to NSF/ANSI 42 and 53 for reduction of the substance listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42 and 53.

## Performance Data\*

Parameter	USEPA MCL	Standard No. 42: Aesthetic Effects		Effluent		Min. Reduc.
		Influent Challenge Concentration	Influent Average	Average	Maximum	
Chlorine	-	2.0 mg/L, 10%	1.86 mg/L	0.051960354 mg/L	0.36 mg/L	97.20% / 98.84% / >99%
T & O	-	-	-	-	-	-
Particulate**	-	at least 10,000 particles/ml	5,700,000 #/ml	30.283 #/ml	69,000 #/ml	99.52% / 98.94% / >99%

Parameter	USEPA MCL	Standard No. 53: Health Effects		Effluent		Min. Reduc.
		Influent Challenge Concentration	Influent Average	Average	Maximum	
Turbidity	1 NTU***	11 ± 1 NTU***	10.7 NTU	0.21 NTU	0.48 NTU	97.99% / 95.20% / 0.5 NTU
Cysts	99.99% Reduction	Minimum 50,000 L	18500 #/L	<1 #/L	<1 #/L	>99.99% / >99.99% / >99.99%
Asbestos	99% Reduction	10 µg/l (MCL, then lower than 0.0005 mg/l)	1.53 MFL	<1 MFL	<1 MFL	>99.93% / >99.99% / >99%
Lead at pH 8.5	0.015 mg/L	0.15 mg/L ± 10%	0.153 mg/L	<0.001 mg/L	<0.001 mg/L	99.33% / 99.29% / 0.010 mg/L
Lead at pH 8.5	0.015 mg/L	0.15 mg/L ± 10%	0.150 mg/L	<0.001 mg/L	<0.001 mg/L	99.33% / 99.29% / 0.010 mg/L
Mercury at pH 8.5	0.002 mg/L	0.02 mg/L ± 10%	0.026 mg/L	0.0003 mg/L	0.0003 mg/L	99.70% / 90.91% / 0.002 mg/L
Mercury at pH 8.5	0.002 mg/L	0.02 mg/L ± 10%	0.026 mg/L	0.0008 mg/L	0.0015 mg/L	88.20% / 75.93% / 0.002 mg/L
Atrazine	0.003 mg/L	0.005 mg/L ± 10%	0.009 mg/L	<0.002 mg/L	<0.002 mg/L	76.89% / 73.31% / 0.003 mg/L
Benzene	0.003 mg/L	0.015 mg/L ± 10%	0.014 mg/L	0.0006 mg/L	0.0011 mg/L	95.71% / 92.14% / 0.003 mg/L
Carbofuran	0.04 mg/L	0.08 mg/L ± 10%	0.081 mg/L	<0.001 mg/L	<0.001 mg/L	99.24% / 96.88% / 0.04 mg/L
Dichlorobenzene	0.075 mg/L	0.225 mg/L ± 10%	0.208 mg/L	<0.0005 mg/L	<0.0005 mg/L	99.76% / 99.74% / 0.075 mg/L
Lindane	0.0002 mg/L	0.002 mg/L ± 10%	0.002 mg/L	0.0000 mg/L	0.0001 mg/L	98.72% / 96.50% / 0.0002 mg/L
Toxaphene	0.0003 mg/L	0.015 mg/L ± 10%	0.015 mg/L	<0.001 mg/L	<0.001 mg/L	92.87% / 91.67% / 0.0003 mg/L

\* Tested using a flow rate of 0.78 gpm; pressure of 60 psig; pH of 7.5 ± 0.5; temp. of 68° ± 5°F (20° ± 3°C)  
\*\* Measurement in Particles/ml. Particles used were 0.5 - 1 microns  
\*\*\* NTU - Nephelometric Turbidity Units

### Operating Specifications

Capacity: certified for up to 750 gallons (2,838 l); up to twelve months.  
Pressure requirement: 35 - 120 psi (2.8-8.2 bar)  
Temperature: 33 - 100°F (0.6-38°C)  
Flow rate: 0.78 gpm (2.9 lpm)



Replacement Element

Tested and Certified by NSF International against NSF/ANSI Standards 42 & 53 in models R0185011 for the reduction of:

Standard No. 42: Aesthetic Effects Taste & Odor Reduction Chlorine Taste & Odor Mechanical Filtration Unit Particulate Reduction Class I	Standard No. 53: Health Effects Chemical Reduction Unit Lead, Atrazine, Lindane, Benzene, Carbofuran, P-Dichlorobenzene, Mercury & Toxaphene Reduction Mechanical Filtration Unit Cyst, Turbidity & Asbestos Reduction
--	--



CUNO Engineered Products, Inc.  
1000 Apollo Road  
Eagan, MN 55121-2240 U.S.A.

651.450.4913  
EPA EST #35917-MN-1

FPO cert